





- Elevator Feel Computer Test Box
- A Safe, Compact, All-Electric Air & Hydraulic Data Tester



- → AIR & HYDRAULIC SUPERVISION IN ONE DEVICE
- → ACCURATE AIR PRESSURE REGULATION
- → HAND WHEEL ADJUSTMENT, RELIEVING DIAPHRAGM RATED AT 6 PSI
- ▶ INTEGRATED PRESSURE RELIEF SAFETY VALVE RATED AT 6 PSI







The EFCTB is a portable tester designed for Boeing's Elevator Feel Computer, situated in the tail of the B737, B747, B757 and B767. The EFCTB is the most compact tester on the market and includes all needed gauges/pumps in a single box. The EFCTB is powered by regular AC in the aft galley of the aircraft, eliminating the need for an external pressure source, as well as keeping the technician safe by removing the need to be behind a running engine on the tarmac.

GENERAL DETAILS		
FULL KIT Physical	Weight: approximately 26 kg Dimensions: (LxHxP) 31.30 x 20.40 x 12.20 in (79.5 x 51.8 x 31 cm)	
TEST BOX Physical	Weight: approximately 6 kg Dimensions: (LxHxP) 13.38 x 11.61 x 6.10 in (34.0 x 29.5 x 15.2 cm)	
	Operating -5°C to 50°C (23°F to 122°F) Storage -20°C to +60°C (-4°F to 140°F) (Extanded Range on-demand)	
External Electrical Supply	100-240 VAC / 50-60 Hz / 60W	
Temperature	Operating: +5°C to +40°C (41°F to 104°F) Storage: +5°C to +40°C (41°F to 104°F)	
Case	Completely weatherproof, meets EMC requirements MIL STD 462D	
Calibration	Recommended period 12 months	
Ease of maintenance	Maintenance limited to calibration, regular external cleaning	

MEASUREMENT RANGES

Function	Range	Accuracy	Max. resolution
Air pressure	0 to 10 psi*	+/- 0.1 % of span	0.001 psi
Hydraulic pressure	0 to 3000 psi	1.0% FS; 0.5% RSS	1 psi

^{*} for safety limited to 6psi

REGULATION OF PRESSURIZED AIR

Hand wheel adjustment, relieving diaphragm rated at 6 psi.

SAFETY AGAINST AIR OVERPRESSURE

Integrated pressure relief safety valve rated at 6 psi.

MAIN FEATURES

Item

EFCTB Unit

Air & hydraulic supervision in one device

Power cord - EU Plug to IEC C13 - 5m

Power cord - UK Plug to IEC C13 - 5m

Power cord - CN Plug to IEC C13 - 5m

Power cord - US Plug to IEC C13 - 5m

Hydraulic transmitter x2

Pitot adaptor x2 For Kit 1055.0

Pitot adaptor x2 For Kit 1055.1

Pitot adaptor x2 For Kit 1055.2

Pitot adaptor x2 For Kit 1055.3

Visco drain hose assembly x2

Hydraulic transmitter (spares) x2

Pitot hose assembly x1

Pretest pin x2

Hose's grip x1 Spares seals kit x1

Lubrication fluid x1

Transport Case

Electrical wire x2

Accurate air pressure regulation

DELIVERY INCLUDED ACCESSORIES

The reference of this kit will be defined as follows:

- The first four digits will be refering to the main device: 1055.
- The fith digit refers to the aircraft range (0 to 4).
- The last digit will define the type of power cord depending of your region (EU, UK, CN or US).

EFCTB Kit Reference [1055.0.000]		
AIRCRAFT COMPLIANCE RANGE	POWER CORD	
0 - Boeing 737 Classic / 737 NG / 737 MAX 1 - Boeing 747 2 - Boeing 757 3 - Boeing 767	0 - Type EU 1 - Type UK 2 - Type CN 3 - Type US	

A FULL RANGE OF SERVICES DEDICATED TO YOUR PERFORMANCE

OUTSTANDING SERVICE Global service & calibration support, 2-day calibration,

Multi-brand Calibration Service, Demo unit rental, Training Maintenance & Repair, Free loan period



More information & Local contact on ateq-aviation.com



ATEQ AVIATION EMEA

Europe, Middle East, Russia, Africa + Custom software/Hardware Requests

15, rue des Dames 78340 Les Clayes-sous-Bois - France Phone: +33-1 30 80 10 20

Fax: +33-1 30 54 11 00



ATEQ AVIATION THE AMERICAS

3216 S. Nordic Rd Arlington Heights, IL 60005 - United States Phone: +1-847-640-6242

Toll Free (USA only): 800-324-2885 Fax: 847-640-8368



ATEQ AVIATION ASIA PACIFIC

38 Jalan Pemimpin #08-06, Singapore 577178 Phone: +65 64511456 Fax: +65 64591190

Ref.

[00481]

[T1-0126]

[T1-0127]

[T1-0128]

[T1-0129]

[ED-0117]

[T1-0394]

[CSA75700HT-3]

[CSA74703-4-4]

[CSA76703-4-4]

[CSA75700-3]

[EFCTB-11P]

[EFCTB-12P]

[BGH1304-4]

[EFCTB-000-04]

[9320104]

[ED-0117]

[DG5050]

[1056.0.000]